



Hurley Muskrat / Otter Exhaust Guards™

Any boat that has a wet exhaust with a discharge opening of about three inches or larger is at risk. A Muskrat, Water Rat,

Otter or other vermins can and will swim up the exhaust to chew through a coupling hose to the inside of the boat or make a den. That also includes boats with underwater exhausts as these rodents & vermins usually look for underwater entrances leading upwards to hollowed out chambers. This is how many boats sink, even while tied to the dock.

Hurley Marine Muskrat Guards™ are 316 stainless steel, adjustable and install inside the exhaust ports. Guards are adjusted outward by stainless rods creating friction to the inside of the port, with no penetration to the hull. Installs in minutes. Protection available in difference sizes depending upon the size of your exhaust.

Size	Part #
3-3/4" to 4-3/4"	MRG-1012A
4-3/4" to 7-1/4"	MRG-1012B
7-1/4" to 8-3/4"	MRG-1012C
8-3/4" to 11"	MRG-1012D

Hurley Marine 10.26.12/ v2.2

© 2012 Hurley Marine, Inc.
All Rights Reserved

Specifications are subject to change without notice.


Trademarks are the property of Hurley Marine, Inc.

Hurley Marine, Inc.
1125 Lake Shore Drive
Escanaba, Michigan 49829
USA
Tel: +1 906.553.6249
sales@hurleymarine.com

Muskrat / Otter Exhaust Guards

Hurley™

Exhaust Guards



Installs in Minutes

- Stainless Steel construction.
- No penetration to the hull.
- Can be installed while the boat is in the water.
- Protective Bolt Caps
- Can be painted
- 1 Year Full-Factory Warranty

Measuring your exhaust port. It's important that we get the correct measurement of both exhaust port holes. We have found that not both exhaust ports are the same size. A 1/4" can make a difference for a bad fit.

To properly measure, take a piece of semi-rigid wire and wrap it around completely in the circumference (inside) of the exhaust port. Lay your wire out and measure that length, now divide that measurement by 3.14 to determine the hole size.